



CL Premiere 1.7/75 ASPHERIC

$f' = 74.9 \text{ mm}$ $\beta_p = 1.918$
 $s_F = -32.6 \text{ mm}$ $s_{EP} = 6.5 \text{ mm}$
 $s_{F'} = 44.9 \text{ mm}$ $s_{AP} = -98.9 \text{ mm}$
 $HH' = -9.9 \text{ mm}$ $\Sigma d = 62.6 \text{ mm}$




RELATIVE ILLUMINATION

The relative illumination is shown for the given focal distances or magnifications.

$f / 1.7$


— $\beta' = 0.0000$ $u'_{max} = 13.9$ $00' = \infty$
 - - $\beta' = 0.0000$ $u'_{max} = 13.9$ $00' = \infty$
 - - - $\beta' = 0.0000$ $u'_{max} = 13.9$ $00' = \infty$



DISTORTION

Distortion is shown for the given focal distances or magnifications. Positive values indicate pincushion distortion and negative values barrel distortion.

— $\beta' = 0.0000$ $u'_{max} = 13.9$ $00' = \infty$
 - - $\beta' = 0.0000$ $u'_{max} = 13.9$ $00' = \infty$
 - - - $\beta' = 0.0000$ $u'_{max} = 13.9$ $00' = \infty$



TRANSMITTANCE

Relative spectral transmittance is shown with reference to wavelength.




Jos. Schneider Optische Werke GmbH
 Ringstrasse 132 55543 Bad Kreuznach Germany

CL Premiere 1.7/75 ASPHERIC

MODULATION with reference to the relative image height

Wavelength λ	[nm]	546	644	610	570	510	480
Spectral weighting	[%]	28.3	4.5	17.8	29.4	16.0	4.0
Spatial frequency R	[1/mm]	20	40	80			
Format	[mm X mm]	18.0	X	21.3			
Diagonal $2u'$	[mm]	27.7					

radial ———
 tangential - - -



Focusing : MTF_{max} at $f / 1.7$, $R = 80$ 1/mm, $u'/u'_{max} = 0$

0.008
-0.148

0.008
-0.148

0.008
-0.148

Printed in the Federal Republic of Germany
 47896 260104